

# EasyGate SPD-R

The EasyGate SPD-R speed gate is a solid compact designed security solution. With a small footprint the SPD is designed for a high level of throughput. Available in a round and square cabinet design.

## MAIN FEATURES

- Low maintenance brushless operation – Patented Magnetic Direct Drive
- Integration of lift control or ticket reader \*
- High resistance to dust and humidity
- Compact cabinet width design: 180mm
- Designed to cope with a high level of throughput
- Alarm signals and audible notifications
- \* Optional upgrade

## DIMENSIONS

Cabinet height: 975mm  
Cabinet length: 1500mm  
Cabinet width: 180mm  
Barrier height: 850mm

## NUMBER OF WINGS

1 Wing/ 2 Wings

## PASSAGE WIDTH

**1 wing**  
Standard width: 550mm  
Max Passage width: 600mm

## 2 wing

Standard width: 650mm  
Max Passage width: 1050mm

## CABINET AND TOP LID

Black Glass Panel

## BASE AND HOUSING

Brushed Stainless Steel (AISI 304)

## BARRIER

Glass Wing (10mm, tempered)

## SIDE INFILL PANEL

6mm tempered glass

## POWER SUPPLY

230V AC



## COMMUNICATION INTERFACE

RS-485/ USB/ Ethernet

## NUMBER OF SENSORS

36 pairs

## TAILGATING AND CROSS OVER DETECTION

Yes

## CLIMBOVER DETECTION

Yes - electronic detection

## RANGE OF OPERATING TEMPERATURE

+10°C to +50°C  
- 25°C to +50°C with heating module

## OPERATING ENVIRONMENT

Indoor

## EMERGENCY MODE

Open manually or automatically  
(with power backup)

## BRAKE CONTROL FUNCTION

Brake force in excess of 650N, Hardened tooth lock brake

## MCBF

10,000,000 cycles (Based on recommended maintenance schedule)

