

FPJ190 2S Security Portal

DIMENSIONS

External Width:	1910mm
External Depth:	1330mm
Internal Width:	1740mm
Internal Depth:	1150mm
Entrance Width:	900mm
Internal Height:	2048mm
External Height:	2320mm
Typical Weight Guideline:	450-660kg

VERSIONS AVAILABLE


KR: Kit and Flush to the floor

POWER SUPPLY

Input:	110 / 230 VAC (EMI Filter included)
Output:	24 Vdc, 5 A/hour
Average Power consumption: (per hour of continuous operation)	35 watt
Max Power consumption:	150 watt
Emergency Battery Back-up:	6-8 hours
Metallic Structure:	Steel 30 / 10

MOTORS

Reversible motors with permanent magnet, working power of 24 Vdc, provided with an encoder for the continuous control of the door position. Doors are provided with electronic control of motor torque for door safety stop in presence of an obstacle.



Features

● Standard Feature ○ Cost Option - Not Available

VERSIONS AVAILABLE

- S version: welded portal structure with 70mm floor base (recessed or surface mounted)
- K version: portal delivered in sections to be assembled at the installation site.
- R version: rail floor guide 12mm base (surface mounted installation only)
- Extended height version
- Extended width version

SAFETY FEATURES

- Anti slip floor mat
- Emergency unlocking device
- Fail secure
- IR safety sensors
- Internal LED light
- Fire alarm signal

SECURITY RATINGS

- FB2/NS EN 1522 top canopy
- FB4/NS EN 1522 metal structure
- Attack resistant class 3 EN 1627-30:2011
- Attack resistant class 4 EN 1627-30:2011

GLASS OPTIONS

- Vandal resistant glass P2A- EN356
- Vandal resistant glass P4A- EN356
- Vandal resistant glass P6B-EN356/ Bullet Resistant glass BR3-EN1063
- Vandal resistant glass PR7B-EN356/ Bullet Resistant glass BR4-EN 1063

CONTROL

- Service mode keyswitch or Multi-function control panel
- Additional multi-function control panel
- Emergency exit control panel
- Night lock

OUTER FINISHING

- RAL colours (sliding door frames RAL 9005 - black)
- Polished steel
- Brushed steel
- Aluminium

DETECTION DEVICES

- Infrared presence sensors
- APD - anti piggybacking device
- Metal detection control
- Pressure mat
- 2 zone pressure mat
- Reed door position tamper sensor

PUSH BUTTON, SIGNALS & REMOTE ACCESS

- Intercom (included in the traffic light)
- LED traffic lights
- Web lan control

EMERGENCY EXIT OPTIONS

- Emergency lever, handle or crank
- Additional Internal emergency lever
- Additional External emergency lever

All Security portal are to be fixed in to the floor through the base of the portal, and on the sides to provide a good stability during security portals operation (it is not a free standing device).

As our policy is to continually improve the products we offer, we reserve the right to amend specifications without prior notice. Further product drawings are available on request